

STANDARD FEATURES

- Lubrication system.
- Magnetic separator.
- Tool box and special wrench.
- Balancing arbor.
- Wheel.
- Wheel chuck.



SGM-600x300



ELECTRICAL CIRCUIT



HYDRAULIC SYSTEM

TYPE	SGM-600x300 (AHR)	SGM-800x400 (AHR)
TABLE DIMENSIONS (mm)	635x305	813x406
MAX. LENGTH TO BE GROUND (mm)	660	910
MAX. WIDTH TO BE GROUND (mm)	340	450
MAX. DISTANCE FROM SPINDLE CENTER TO TABLE (mm)	580	580
MAX HORIZONTAL TRAVEL (m / min)	7-25	7-25
MAX. LONGITUDINAL TRAVEL (automatic feed) (mm)	0,1-8	0,1-8
LONGITUDINAL SPINDLE SPEED (mm / min)	990	990
WHEEL DIMENSIONS (mm)	350x40x127	400x40x127
WHEEL SPEED (rpm)	1450	1450
POWER (kW)	8,5	8,5
MAX. WEIGHT OF PROCESS MATERIAL (with the magnet) (kg)	270	500
WEIGHT (kg)	2800	3800
OVERALL DIMENSIONS (LxWxH) (mm)	2350x2200x2150	3600x2400x1890